

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 5/22/2023 Revision date: 7/31/2023 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : GILDED WHITE PUMPKIN #EU55232F

UFI : C9PT-R9VT-T002-FQQN

Product code : EU55232F

Type of product : Perfumes, fragrances
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

Use of the substance/mixture : Perfumes, fragrances
Function or use category : Odour agents

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE International GmbH

Mittlerer Weg 35 DE- 79424 Auggen

Germany

T 49-7631-931-8900

SDS@frenchcolor.com - www.frenchcolor.com

### 1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Warr

Contains : Vertenex; Cinnamic aldehyde; COUMARIN; 3(2H)-Furanone, 4-hydroxy-2,5-dimethyl-

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Extra phrases : For professional users only.

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Vertenex	CAS-No.: 32210-23-4 EC-No.: 250-954-9 REACH-no: 01-2119976286- 24	3.1 – 6.25	Skin Sens. 1B, H317
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 REACH-no: 01-2119935242- 45	3.1 – 6.16	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-	2.5 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60	0.7 – 1.4	Eye Irrit. 2, H319
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	0.5 – 0.94	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	0.3 – 0.54	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ethyl lactate substance with national workplace exposure limit(s) (FI, LT, SE)	CAS-No.: 97-64-3 EC-No.: 202-598-0 EC Index-No.: 607-129-00-7	0.3 – 0.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
1,2-Propanediol substance with national workplace exposure limit(s) (GB, HR, IE, LT, LV, PL, NO)	CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809- 23	0.1 – 0.257	Not classified
Oenanthic ether (Ethyl heptanoate)	CAS-No.: 106-30-9 EC-No.: 203-382-9	0.1 – 0.25	Flam. Liq. 3, H226 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Furfural substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, PL, PT, RO, SE, SK, NO, CH)	CAS-No.: 98-01-1 EC-No.: 202-627-7 EC Index-No.: 605-010-00-4	0.1 – 0.2	Flam. Liq. 3, H226 Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335 Aquatic Chronic 3, H412
Isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.1 – 0.2	Flam. Liq. 2, H225 STOT SE 3, H336
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl-	CAS-No.: 3658-77-3 EC-No.: 222-908-8	0 – 0.04	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Irrit. 2, H319 Skin Sens. 1A, H317
.betaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	≤ 0.00225	Flam. Liq. 3, H226
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	≤ 0.00186	Not classified
.alphaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 80-56-8 EC-No.: 201-291-9	≤ 0.00015	Flam. Liq. 3, H226

Full text of H- and EUH-statements: see section 16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to

breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water.

Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated

clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

Rinse immediately with plenty of water. Obtain medical attention if pair

: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

## 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

7/31/2023 (Revision date) EN (English) 4/31

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products Strong bases. Strong acids. Incompatible materials Sources of ignition. Direct sunlight.

Storage temperature 25 °C

Storage area Store in a well-ventilated place. Store away from heat.

Special rules on packaging Store in a closed container Do not store in corrodable metal. Packaging materials

#### 7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Benzyl alcohol (100-51-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	40 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	45 mg/m³	
HTP (OEL TWA) [2]	10 ppm	

# Safety Data Sheet

Benzyl alcohol (100-51-6)		
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
OEL chemical category	Skin notation	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	22 mg/m³	
OEL TWA [ppm]	5 ppm	
OEL STEL	44 mg/m³	
OEL STEL [ppm]	10 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	22 mg/m³ (aerosol, vapour)	
MAK (OEL TWA) [2]	5 ppm (aerosol, vapour)	
OEL chemical category	Skin notation	
Ethyl lactate (97-64-3)		
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	25 mg/m³	
HTP (OEL TWA) [2]	5 ppm	
HTP (OEL STEL)	49 mg/m³	
HTP (OEL STEL) [ppm]	10 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	25 mg/m³	
IPRV (OEL TWA) [ppm]	5 ppm	
TPRV (OEL STEL)	50 mg/m³	
TPRV (OEL STEL) [ppm]	10 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	25 mg/m³ (same limit value expressed in ppm shall be applied for those lactates for which no limit values have been defined)	
NGV (OEL TWA) [ppm]	5 ppm (same limit value expressed in ppm shall be applied for those lactates for which no limit values have been defined)	

# Safety Data Sheet

Ethyl lactate (97-64-3)			
KTV (OEL STEL)	50 mg/m³ (same limit value expressed in ppm shall be applied for those lactates for which no limit values have been defined)		
KTV (OEL STEL) [ppm]	10 ppm (same limit value expressed in ppm shall be applied for those lactates for which no limit values have been defined)		
1,2-Propanediol (57-55-6)			
Croatia - Occupational Exposure Limits			
GVI (OEL TWA) [1]	474 mg/m³ (total vapor and particles) 10 mg/m³ (particles)		
GVI (OEL TWA) [2]	150 ppm		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	10 mg/m³ (particulates) 470 mg/m³ (total vapour and particulates)		
OEL TWA [2]	150 ppm (total vapour and particulates)		
OEL STEL	1410 mg/m³ (calculated-particulates) 30 mg/m³ (calculated)		
OEL STEL [ppm]	450 ppm (calculated-total vapour and particulates)		
Latvia - Occupational Exposure Limits			
OEL TWA	7 mg/m³		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	7 mg/m³		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	100 mg/m³ (vapor and inhalable fraction)		
United Kingdom - Occupational Exposure Limits	United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	474 mg/m³ (total vapour and particulates) 10 mg/m³ (particulates)		
WEL TWA (OEL TWA) [2]	150 ppm (total vapour and particulates)		
WEL STEL (OEL STEL)	1422 mg/m³ (calculated-total vapour and particulates) 30 mg/m³ (calculated-particulate)		
WEL STEL (OEL STEL) [ppm]	450 ppm (calculated-total vapour and particulates)		
Norway - Occupational Exposure Limits			
Grenseverdi (OEL TWA) [1]	79 mg/m³		
Grenseverdi (OEL TWA) [2]	25 ppm		
Korttidsverdi (OEL STEL)	118.5 mg/m³ (value calculated)		
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)		
Furfural (98-01-1)			
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	20 mg/m³		
MAK (OEL TWA) [ppm]	5 ppm		
OEL chemical category	Skin notation, Group B Carcinogen		
Belgium - Occupational Exposure Limits			
OEL TWA	8 mg/m³		

# Safety Data Sheet

Furfural (98-01-1)		
OEL TWA [ppm]	2 ppm	
OEL chemical category	Skin	
Bulgaria - Occupational Exposure Limits		
OEL TWA	10 mg/m³ (Furfurol)	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	8 mg/m³	
GVI (OEL TWA) [2]	2 ppm	
KGVI (OEL STEL)	20 mg/m³	
KGVI (OEL STEL) [ppm]	5 ppm	
OEL chemical category	Skin notation	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	10 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	7.9 mg/m³	
OEL TWA [2]	2 ppm	
OEL STEL	15.8 mg/m³	
OEL STEL [ppm]	4 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	8 mg/m³	
OEL TWA [ppm]	2 ppm	
OEL STEL	20 mg/m³	
OEL STEL [ppm]	5 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	8 mg/m³	
HTP (OEL TWA) [2]	2 ppm	
HTP (OEL STEL)	20 mg/m³	
HTP (OEL STEL) [ppm]	5 ppm	
OEL chemical category	Potential for cutaneous absorption	
France - Occupational Exposure Limits		
VLE (OEL C/STEL)	8 mg/m³	
VLE (OEL C/STEL) [ppm]	2 ppm	
OEL chemical category	Carcinogen category 2	
France - Biological limit values		
BLV	Parameter: Total furoic acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)	

# Safety Data Sheet

Furfural (98-01-1)		
Greece - Occupational Exposure Limits		
OEL TWA	20 mg/m³	
OEL TWA [ppm]	5 ppm	
OEL STEL	40 mg/m³	
OEL STEL [ppm]	10 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	8 mg/m³	
CK (OEL STEL)	20 mg/m³	
OEL chemical category	Sensitizer, Potential for cutaneous absorption	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	8 mg/m³	
OEL TWA [2]	2 ppm	
OEL STEL	20 mg/m³	
OEL STEL [ppm]	5 ppm	
OEL chemical category	Potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	8 mg/m³	
IPRV (OEL TWA) [ppm]	2 ppm	
TPRV (OEL STEL)	20 mg/m³	
TPRV (OEL STEL) [ppm]	5 ppm	
OEL chemical category	Carcinogen, Skin notation	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	25 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA [ppm]	2 ppm	
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, skin - potential for cutaneous exposure	
Romania - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
OEL TWA [ppm]	2.5 ppm	
OEL STEL	15 mg/m³	
OEL STEL [ppm]	4 ppm	
OEL chemical category	C2	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	7.9 mg/m³	

# Safety Data Sheet

Furfural (98-01-1)		
NPHV (OEL TWA) [2]	2 ppm	
OEL chemical category	Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	8 mg/m³	
VLA-ED (OEL TWA) [2]	2 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Spain - Biological limit values		
BLV	200 mg/l Parameter: Furoic acid - Medium: urine - Sampling time: end of shift (with hydrolysis)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	8 mg/m³	
NGV (OEL TWA) [ppm]	2 ppm	
KTV (OEL STEL)	20 mg/m³	
KTV (OEL STEL) [ppm]	5 ppm	
OEL chemical category	Skin notation	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	8 mg/m³	
WEL TWA (OEL TWA) [2]	2 ppm	
WEL STEL (OEL STEL)	20 mg/m³	
WEL STEL (OEL STEL) [ppm]	5 ppm	
WEL chemical category	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	8 mg/m³	
Grenseverdi (OEL TWA) [2]	2 ppm	
Korttidsverdi (OEL STEL)	16 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	4 ppm (value calculated)	
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	8 mg/m³	
MAK (OEL TWA) [2]	2 ppm	
OEL chemical category	Skin notation	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	0.2 ppm	
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, Skin - potential significant contribution to overall exposure by the cutaneous route	
USA - ACGIH - Biological Exposure Indices		
BEI	200 mg/l Parameter: Furoic acid with hydrolysis - Medium: urine - Sampling time: end of shift (nonspecific)	

# Safety Data Sheet

Isobutyl acetate (110-19-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	241 mg/m³ (Butyl acetates)	
MAK (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
MAK (OEL STEL)	480 mg/m³ (Butyl acetate)	
MAK (OEL STEL) [ppm]	100 ppm (Butyl acetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	238 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	712 mg/m³	
OEL STEL [ppm]	150 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	241 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
KGVI (OEL STEL)	723 mg/m³	
KGVI (OEL STEL) [ppm]	150 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	241 mg/m³	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	241 mg/m³ (Butyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Butyl acetate, all isomers)	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	240 mg/m³ (Butyl acetate)	

# Safety Data Sheet

Isobutyl acetate (110-19-0)		
HTP (OEL TWA) [2]	50 ppm (Butyl acetate)	
HTP (OEL STEL)	725 mg/m³ (Butyl acetate)	
HTP (OEL STEL) [ppm]	150 ppm (Butyl acetate)	
France - Occupational Exposure Limits		
VME (OEL TWA)	241 mg/m³ (restrictive limit)	
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)	
VLE (OEL C/STEL)	723 mg/m³ (restrictive limit)	
VLE (OEL C/STEL) [ppm]	150 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 90	00)	
AGW (OEL TWA) [1]	300 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	62 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Greece - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	241 mg/m³	
CK (OEL STEL)	723 mg/m³	
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	241 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	723 mg/m³ (calculated)	
OEL STEL [ppm]	150 ppm (calculated)	
Italy - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	241 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	723 mg/m³	
TPRV (OEL STEL) [ppm]	150 ppm	

# Safety Data Sheet

Isobutyl acetate (110-19-0)		
Luxembourg - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	241 mg/m³	
TGG-8u (OEL TWA) [ppm]	50 ppm	
TGG-15min (OEL STEL)	723 mg/m³	
TGG-15min (OEL STEL) [ppm]	150 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
NDSCh (OEL STEL)	720 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	241 mg/m³ (indicative limit value)	
OEL TWA [ppm]	50 ppm (indicative limit value)	
OEL STEL	723 mg/m³ (indicative limit value)	
OEL STEL [ppm]	150 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	480 mg/m³	
NPHV (OEL TWA) [2]	100 ppm	
NPHV (OEL C)	700 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	241 mg/m³	

# Safety Data Sheet

Isobutyl acetate (110-19-0)		
VLA-ED (OEL TWA) [2]	50 ppm	
VLA-EC (OEL STEL)	723 mg/m³	
VLA-EC (OEL STEL) [ppm]	150 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	241 mg/m³ (Butyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
KTV (OEL STEL)	723 mg/m³ (Butyl acetates)	
KTV (OEL STEL) [ppm]	150 ppm (Butyl acetates)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	903 mg/m³	
WEL STEL (OEL STEL) [ppm]	187 ppm	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	241 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	723 mg/m³ (value from the regulation)	
Korttidsverdi (OEL STEL) [ppm]	150 ppm (value from the regulation)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	240 mg/m³	
MAK (OEL TWA) [2]	50 ppm	
KZGW (OEL STEL)	720 mg/m³	
KZGW (OEL STEL) [ppm]	150 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)	
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)	
Dipropylene glycol monomethyl ether (34590-94-8)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	308 mg/m³	
IOEL TWA [ppm]	50 ppm	
Remark	Possibility of significant uptake through the skin	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	307 mg/m³ (mixed isomers)	
MAK (OEL TWA) [ppm]	50 ppm (mixed isomers)	
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)	
MAK (OEL STEL) [ppm]	100 ppm (isomers mixtures)	
OEL chemical category	Skin notation	
Belgium - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	•	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
OEL TWA [ppm]	50 ppm		
OEL chemical category	Skin, Skin notation		
Bulgaria - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
Croatia - Occupational Exposure Limits			
GVI (OEL TWA) [1]	308 mg/m³		
GVI (OEL TWA) [2]	50 ppm		
OEL chemical category	Skin notation		
Cyprus - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	Skin-potential for cutaneous absorption		
Czech Republic - Occupational Exposure Limits			
PEL (OEL TWA)	270 mg/m³		
OEL chemical category	Potential for cutaneous absorption		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	309 mg/m³		
OEL TWA [2]	50 ppm		
OEL STEL	618 mg/m³		
OEL STEL [ppm]	100 ppm		
OEL chemical category	Potential for cutaneous absorption		
Estonia - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	Skin notation		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	310 mg/m³		
HTP (OEL TWA) [2]	50 ppm		
OEL chemical category	Potential for cutaneous absorption		
France - Occupational Exposure Limits	France - Occupational Exposure Limits		
VME (OEL TWA)	308 mg/m³ (restrictive limit)		
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)		
OEL chemical category	Risk of cutaneous absorption		
Germany - Occupational Exposure Limits (TRGS 900)			
AGW (OEL TWA) [1]	310 mg/m³ (isomer mixture)		
AGW (OEL TWA) [2]	50 ppm (isomer mixture)		
Gibraltar - Occupational Exposure Limits			
OEL TWA	308 mg/m³		

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	600 mg/m³	
OEL TWA [ppm]	100 ppm	
OEL STEL	900 mg/m³	
OEL STEL [ppm]	150 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	308 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	308 mg/m³ ((2-Methoxymethylethoxy)propanol)	
OEL TWA [2]	50 ppm ((2-Methoxymethylethoxy)propanol)	
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)	
OEL STEL [ppm]	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)	
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	skin - potential for cutaneous exposure	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
IPRV (OEL TWA) [ppm]	50 ppm (2-(2-Methoxypropoxy)-propanol)	
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
TPRV (OEL STEL) [ppm]	75 ppm (2-(2-Methoxypropoxy)-propanol)	
OEL chemical category	Skin notation	
Luxembourg - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Malta - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Possibility of significant uptake through the skin	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
Netherlands - Occupational Exposure Limits			
TGG-8u (OEL TWA)	300 mg/m³		
TGG-8u (OEL TWA) [ppm]	48.7 ppm		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-1-ol)		
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)		
Portugal - Occupational Exposure Limits			
OEL TWA	308 mg/m³ (indicative limit value)		
OEL TWA [ppm]	50 ppm (indicative limit value)		
OEL STEL [ppm]	150 ppm		
OEL chemical category	skin - potential for cutaneous exposure indicative limit value		
Romania - Occupational Exposure Limits	·		
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	Skin notation		
Slovakia - Occupational Exposure Limits			
NPHV (OEL TWA) [1]	308 mg/m³		
NPHV (OEL TWA) [2]	50 ppm		
OEL chemical category	Potential for cutaneous absorption		
Slovenia - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	308 mg/m³		
OEL STEL [ppm]	50 ppm		
OEL chemical category	Potential for cutaneous absorption		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	308 mg/m³ (indicative limit value)		
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)		
OEL chemical category	skin - potential for cutaneous absorption		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	300 mg/m³		
NGV (OEL TWA) [ppm]	50 ppm		
KTV (OEL STEL)	450 mg/m³		
KTV (OEL STEL) [ppm]	75 ppm		
OEL chemical category	Skin notation		
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	308 mg/m³		
WEL TWA (OEL TWA) [2]	50 ppm		

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
WEL STEL (OEL STEL)	924 mg/m³ (calculated)		
WEL STEL (OEL STEL) [ppm]	150 ppm (calculated)		
WEL chemical category	Potential for cutaneous absorption		
Norway - Occupational Exposure Limits			
Grenseverdi (OEL TWA) [1]	300 mg/m³		
Grenseverdi (OEL TWA) [2]	50 ppm		
Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)		
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)		
OEL chemical category	Skin notation		
Switzerland - Occupational Exposure Limits			
MAK (OEL TWA) [1]	300 mg/m³ (aerosol, vapour)		
MAK (OEL TWA) [2]	50 ppm (aerosol, vapour)		
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)		
KZGW (OEL STEL) [ppm]	50 ppm (aerosol, vapour)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA [ppm]	50 ppm (Dipropylene glycol methyl ether)		
.alphaPinene (80-56-8)	.alphaPinene (80-56-8)		
Belgium - Occupational Exposure Limits			
OEL TWA [ppm]	20 ppm		
Estonia - Occupational Exposure Limits			
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
OEL TWA [ppm]	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
OEL STEL [ppm]	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	150 mg/m³		
IPRV (OEL TWA) [ppm]	25 ppm		
TPRV (OEL STEL)	300 mg/m³		
TPRV (OEL STEL) [ppm]	50 ppm		
Portugal - Occupational Exposure Limits			
OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)		
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	113 mg/m³		
VLA-ED (OEL TWA) [2]	20 ppm		
OEL chemical category	Sensitizer		

# Safety Data Sheet

alaba Birana (60 50 0)		
.alphaPinene (80-56-8)		
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	150 mg/m³	
NGV (OEL TWA) [ppm]	25 ppm	
KTV (OEL STEL)	300 mg/m³	
KTV (OEL STEL) [ppm]	50 ppm	
OEL chemical category	Sensitizer	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	140 mg/m³	
Grenseverdi (OEL TWA) [2]	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)	
OEL chemical category	Skin notation	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer	
.betaPinene (127-91-3)		
Belgium - Occupational Exposure Limits		
OEL TWA [ppm]	20 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
OEL TWA [ppm]	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
OEL STEL [ppm]	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	150 mg/m³	
IPRV (OEL TWA) [ppm]	25 ppm	
TPRV (OEL STEL)	300 mg/m³	
TPRV (OEL STEL) [ppm]	50 ppm	
Portugal - Occupational Exposure Limits		
OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	113 mg/m³	
VLA-ED (OEL TWA) [2]	20 ppm	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.betaPinene (127-91-3)		
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	150 mg/m³	
NGV (OEL TWA) [ppm]	25 ppm	
KTV (OEL STEL)	300 mg/m³	
KTV (OEL STEL) [ppm]	50 ppm	
OEL chemical category	Sensitizer	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	140 mg/m³	
Grenseverdi (OEL TWA) [2]	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer	

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

## 8.1.5. Control banding

No additional information available

# 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

### Personal protective equipment:

Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):





### 8.2.2.1. Eye and face protection

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

# 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear protective gloves.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Wear appropriate mask

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard. light yellow. amber.

: Not available

: Not applicable

Odour : characteristic. Odour threshold : Not available Melting point : Not applicable Freezing point : Not available Boiling point : Not available Flammability : Not applicable **Explosive limits** : Not available : Not available Lower explosion limit Upper explosion limit : Not available Flash point : 96 °C Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic : Not available : Not available Solubility Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapour pressure : Not available Vapour pressure at 50°C Density : Not available Relative density : Not available

#### 9.2. Other information

Particle characteristics

Relative vapour density at 20°C

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

## 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation)	: Not classified	
Vertenex (32210-23-4)		
LD50 oral rat	5 g/kg (Source: NLM_CIP)	
LD50 oral	3370 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)	
Cinnamic aldehyde (104-55-2)		
LD50 oral rat	2220 mg/kg (Source: NLM_CIP)	
LD50 oral	2200 mg/kg bodyweight	
LD50 dermal rabbit	1260 mg/kg (Source: EPA_HPV)	
LD50 dermal	1100 mg/kg bodyweight	
Benzyl alcohol (100-51-6)		
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)	
LD50 oral	1620 mg/kg bodyweight	
LD50 dermal	2500 mg/kg bodyweight	
Vanillin (121-33-5)		
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)	
LD50 dermal	2600 mg/kg bodyweight	
COUMARIN (91-64-5)		
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)	
LD50 oral	290 mg/kg bodyweight	
LD50 dermal rat	293 mg/kg (Source: ECHA_API)	
Benzyl benzoate (120-51-4)		
LD50 oral rat	500 mg/kg (Source: NLM_CIP)	
LD50 oral	1160 mg/kg bodyweight	
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)	
Ethyl lactate (97-64-3)		
LD50 oral rat	8200 mg/kg (Source: NLM_CIP)	
LD50 oral	2500 mg/kg bodyweight	

7/31/2023 (Revision date) EN (English) 22/31

# Safety Data Sheet

Ethyl lactate (97-64-3)	
LD50 dermal rabbit	> 5 g/kg (Source: NLM_HSDB)
1,2-Propanediol (57-55-6)	
LD50 oral rat	20 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	20800 mg/kg (Source: NLM_CIP)
Oenanthic ether (Ethyl heptanoate) (106-30-9)	
LD50 oral rat	> 34640 mg/kg (Source: NLM_CIP)
Furfural (98-01-1)	
LD50 oral rat	125 mg/kg (Source: JAPAN_GHS)
LD50 oral	100 mg/kg bodyweight
LD50 dermal rabbit	500 – 1000 mg/kg (Source: JAPAN_GHS)
LD50 dermal	1100 mg/kg bodyweight
LC50 Inhalation - Rat	756 mg/m³ (Exposure time: 1 h Source: WHO)
LC50 Inhalation - Rat (Vapours)	1 mg/l/4h
Isobutyl acetate (110-19-0)	
LD50 oral rat	15400 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 17400 mg/kg (Source: NLM_CIP)
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (365	8-77-3)
LD50 oral	1608 mg/kg bodyweight
Dipropylene glycol monomethyl ether (34590-	94-8)
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
.alphaPinene (80-56-8)	
LD50 oral rat	3700 mg/kg (Source: NLM_CIP)
LD50 oral	500 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg (Source: CHEMVIEW)
.betaPinene (127-91-3)	
LD50 oral rat	> 5000 mg/kg (Source: EPA_HPV)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
	Causes skin irritation.
	Causes serious eye irritation.
Respiratory or skin sensitisation :	May cause an allergic skin reaction.
Germ cell mutagenicity :	Not classified Not classified
,	INUL CIASSIIIEU
COUMARIN (91-64-5)	2. Not classifiable
IARC group	3 - Not classifiable
Furfural (98-01-1)	O. Nick described.
IARC group	3 - Not classified
Reproductive toxicity : STOT-single exposure :	Not classified Not classified
	·····

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl lactate (97-64-3)	
STOT-single exposure	May cause respiratory irritation.
Furfural (98-01-1)	
STOT-single exposure	May cause respiratory irritation.
Isobutyl acetate (110-19-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
Benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s

# 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Hazardous to the aquatic environment, short–term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term

(chronic)

: Not classified

8.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static] Source: ECHA)
460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
23 mg/l (Exposure time: 48 h - Species: water flea)
53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
0.168 mg/l
51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)

# Safety Data Sheet

1,2-Propanediol (57-55-6)			
LC50 - Fish [2]	41 – 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)		
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])		
EC50 96h - Algae [1]	19000 mg/l (Species: Pseudokirchneriella subcapitata)		
Furfural (98-01-1)			
LC50 - Fish [1]	13.4 – 19.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)		
LC50 - Fish [2]	16.79 – 26.35 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)		
Isobutyl acetate (110-19-0)			
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes Source: ECHA)		
Dipropylene glycol monomethyl ether (34590-	94-8)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])		
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
.alphaPinene (80-56-8)			
LC50 - Fish [1]	0.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)		
EC50 - Crustacea [1]	41 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
12.2. Persistence and degradability	12.2. Persistence and degradability		
GILDED WHITE PUMPKIN #EU55232F			
Persistence and degradability	Not established.		
Benzyl benzoate (120-51-4)			
Persistence and degradability	May cause long-term adverse effects in the environment.		
12.3. Bioaccumulative potential			
GILDED WHITE PUMPKIN #EU55232F			
Bioaccumulative potential	Not established.		
Vertenex (32210-23-4)			
Partition coefficient n-octanol/water (Log Pow)	4.8 (at 25 °C)		
Cinnamic aldehyde (104-55-2)			
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)		
Benzyl alcohol (100-51-6)			
Partition coefficient n-octanol/water (Log Pow)	1.05		
Vanillin (121-33-5)			
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)		
Benzyl benzoate (120-51-4)			
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)		
Bioaccumulative potential	Not established.		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl lactate (97-64-3)		
Partition coefficient n-octanol/water (Log Pow)	0.7 (at 25 °C (at pH >2-<8)	
1,2-Propanediol (57-55-6)		
BCF - Fish [1]	(1 dimensionless)	
Partition coefficient n-octanol/water (Log Pow)	-1.07 (at 20.5 °C (at pH >=6.2-<=6.4)	
Oenanthic ether (Ethyl heptanoate) (106-30-9)		
Partition coefficient n-octanol/water (Log Pow)	3.98 (at 35 °C (at pH 7)	
Furfural (98-01-1)		
Partition coefficient n-octanol/water (Log Pow)	0.67	
Isobutyl acetate (110-19-0)		
BCF - Fish [1]	(no significant bioconcentration)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7)	
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (3658-77-3)		
Partition coefficient n-octanol/water (Log Pow)	0.95 (at 20 °C (at pH 2.5)	
Dipropylene glycol monomethyl ether (34590-94-8)		
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	
.alphaPinene (80-56-8)		
Partition coefficient n-octanol/water (Log Pow)	4.1	

# 12.4. Mobility in soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Waste treatment methods Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

: Dispose in a safe manner in accordance with local/national regulations.

: Avoid release to the environment.

Ecology - waste materials

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

- : HP3 "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

## 14.6. Special precautions for user

#### **Overland transport**

Not applicable

#### Transport by sea

Not applicable

## Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

# 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Ethyl lactate; Oenanthic ether (Ethyl heptanoate); Furfural; Isobutyl acetate; .alphaPinene; .betaPinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	GILDED WHITE PUMPKIN #EU55232F; Vertenex; Cinnamic aldehyde; Benzyl alcohol ; Benzyl benzoate; Ethyl lactate; Furfural; Isobutyl acetate; 3(2H)-Furanone, 4-hydroxy-2,5-dimethyl-	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Cinnamic aldehyde ; Benzyl benzoate ; Oenanthic ether (Ethyl heptanoate) ; Furfural	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Ethyl lactate; Oenanthic ether (Ethyl heptanoate); Furfural; Isobutyl acetate; .alphaPinene; .betaPinene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

## **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 15.1.2. National regulations

#### France

Occupational diseases		
Code	Description	
RG 74	Occupational disorders caused by furfural and furfuryl alcohol	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

#### Germany

Water hazard class (WGK) Storage class (LGK, TRGS 510)

Joint storage table

: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

: LGK 10 - Combustible liquids.

	•			
LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

Joint storage with restrictions permitted for

Joint storage permitted for

: LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7.

: LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2.

 $: \; \mathsf{LGK} \; \mathsf{2B}, \; \mathsf{LGK} \; \mathsf{3}, \; \mathsf{LGK} \; \mathsf{4.1B}, \; \mathsf{LGK} \; \mathsf{6.1A}, \; \mathsf{LGK} \; \mathsf{6.1B}, \; \mathsf{LGK} \; \mathsf{6.1C}, \; \mathsf{LGK} \; \mathsf{6.1D}, \; \mathsf{LGK} \; \mathsf{8A}, \; \mathsf{LGK} \; \mathsf{8B}, \\$ 

LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.

List of sensitizing substances (TRGS 907) : 0

Hazardous Incident Ordinance (12. BImSchV)

: Contains sensitizing substances according TRGS 907.: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

ABM category

: A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen – Borstvoeding

SZW-lijst van reprotoxische stoffen –

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

None of the components are listedNone of the components are listedNone of the components are listed

: None of the components are listed

: None of the components are listed

#### Denmark

Class for fire hazard

Store unit

Classification remarks

: Class III-1 : 50 liter

: Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

#### **Switzerland**

Storage class (LK) : LK 10/12 - Liquids

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Other information : None.

7/31/2023 (Revision date) EN (English) 29/31

# Safety Data Sheet

Full text of H- and EUH	Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3		
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3		
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Carc. 2	Carcinogenicity, Category 2		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H311	Toxic in contact with skin.		
H312	Harmful in contact with skin.		
H314	Causes severe skin burns and eye damage.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H351	Suspected of causing cancer.		
H400	Very toxic to aquatic life.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
Skin Sens. 1	Skin sensitisation, Category 1		
Skin Sens. 1A	Skin sensitisation, category 1A		
Skin Sens. 1B	Skin sensitisation, category 1B		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.