OUD & AMBER CLP #EU58083F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 10/28/2025 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Trade name	:	OUD & AMBER CLP #EU58083F
UFI	:	WUXR-9CXM-T00Q-3G5S
Product code	:	EU58083F
Type of product	:	Perfumes, fragrances
Product group	:	Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	:	Professional use,Industrial use
Industrial/Professional use spec	:	Industrial For professional use only
Use of the substance/mixture	:	Perfumes, fragrances
Function or use category	:	Odour agents

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE INTERNATIONAL GmbH
Mittlerer Weg 35
DE 79424 Auggen
Germany
T 49-7631-931-8900
SDS@frenchcolor.com, www.frenchcolor.com

1.4. Emergency telephone number

Emergency number	:	1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07 GHS09

Signal word (CLP)	:	Warning
Contains	:	Cedryl acetate; Linalyl acetate; Cashmeran; (ETHOXYMETHOXY)CYCLODODECANE; Clove Leaf Oil ; COUMARIN; Linalool; Orange oil
Hazard statements (CLP)	:	H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P321 - Specific treatment (see supplemental first aid instruction on this label).

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cedryl acetate	CAS-No.: 77-54-3 EC-No.: 201-036-1	3 – 6	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1B, H317
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314-33	2.5 – 5	Aquatic Chronic 2, H411
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans)	CAS-No.: 63500-71-0 EC-No.: 405-040-6 EC Index-No.: 603-101-00-3 REACH-no: 01-000015458-64	0.45 – 1.8	Eye Irrit. 2, H319
reaction mass of: (E)-oxacyclohexadec-12-en-2-one; (E)-oxacyclohexadec-13-en-2-one; a) (Z)-oxacyclohexadec-(12)-en-2-one and b) (Z)-oxacyclohexadec-(13)-en-2-one	CAS-No.: 111879-80-2 EC-No.: 422-320-3 EC Index-No.: 606-092-00-4	0.9 – 1.7	Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Patchouli oil	CAS-No.: 8014-09-3 EC-No.: 616-944-7 EC Index-No.: 616-944-7	0.6 – 1.1	Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Linalyl acetate	CAS-No.: 115-95-7 EC-No.: 204-116-4 REACH-no: 01-2119454789-19	0.4 – 0.8	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Cashmeran	CAS-No.: 33704-61-9 EC-No.: 251-649-3 REACH-no: 01-2119977131-40	0.4 – 0.8	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT RE 2, H373 Aquatic Chronic 2, H411
Sandal Mysore Core	CAS-No.: 28219-60-5 EC-No.: 248-907-2	0.4 – 0.8	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
(ETHOXYMETHOXY)CYCLODODECANE	CAS-No.: 58567-11-6 EC-No.: 261-332-1	0.4 – 0.8	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	0.4 – 0.8	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353-35	0.4 – 0.7	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Carbitol substance with national workplace exposure limit(s) (AT, DE, EE, SE, SI, CH)	CAS-No.: 111-90-0 EC-No.: 203-919-7 REACH-no: 01-2119475105-42	0.28932 – 0.622038	Not classified
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.3 – 0.6	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Clove Leaf Oil	CAS-No.: 8000-34-8 EC-No.: 616-772-2	0.2 – 0.4	Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.000254 – 0.0003683	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.00000435	Not classified

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

Joint storage table :

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2

Joint storage permitted for : LGK 2B, LGK 3, LGK 4.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Carbitol (111-90-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	35 mg/m³
	6 ppm
MAK (OEL STEL)	140 mg/m³
	24 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	50.1 mg/m³

Carbitol (111-90-0)	
	10 ppm
OEL chemical category	Skin notation
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	35 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	6 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Slovenia - Occupational Exposure Limits	
OEL TWA	35 mg/m³
	6 ppm
OEL STEL	70 mg/m³
	12 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	80 mg/m³
	15 ppm
KGV (OEL STEL)	170 mg/m³
	30 ppm
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	50 mg/m³ (aerosol, inhalable dust, vapour)
KZGW (OEL STEL)	100 mg/m³ (aerosol, inhalable dust, vapour)

Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm

Dipropylene glycol monomethyl ether (34590-94-8)	
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m³
	50 ppm
OEL STEL	618 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m³ (restrictive limit)
	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m³ (isomer mixture)
	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m³
	100 ppm

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL STEL	900 mg/m³
	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)

Dipropylene glycol monomethyl ether (34590-94-8)	
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL STEL	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m³
	50 ppm
KGV (OEL STEL)	450 mg/m³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m³

Dipropylene glycol monomethyl ether (34590-94-8)	
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	50 ppm (Dipropylene glycol methyl ether)

Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m³
	50 ppm
IOEL STEL	384 mg/m³
	100 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
MAK (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m³
	20 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift

Toluene (108-88-3)	
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	192 mg/m³
	50 ppm
KGVI (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m³
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m³
	25 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m³

Toluene (108-88-3)	
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m³
	25 ppm
HTP (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m³ (restrictive limit)
	20 ppm (restrictive limit)
VLE (OEL C/STEL)	384 mg/m³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of exposure or shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: at the end of the shift, in case of long-term exposure after several previous shifts
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation

Toluene (108-88-3)	
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190 mg/m³
CK (OEL STEL)	384 mg/m³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of exposure (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: at the end of exposure or shift (after hydrolysis)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m³
	50 ppm
TPRV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm

Toluene (108-88-3)	
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³
NDSCh (OEL STEL)	200 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m³
	50 ppm
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption

Toluene (108-88-3)	
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m³
	50 ppm
KGV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)

Toluene (108-88-3)	
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
KZGW (OEL STEL)	760 mg/m³
	200 ppm
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 µmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 µmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 µg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	20 ppm
ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:
Avoid all unnecessary exposure.
Personal protective equipment symbol(s):



Eye and face protection

Eye protection:
Chemical goggles or safety glasses. Safety glasses

Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Wear protective gloves.

Respiratory protection

Respiratory protection:
Wear appropriate mask

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.
Other information:
Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Conforms to standard.
Odour	:	characteristic.
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not applicable
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	> 93.3 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	Not available
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	0.000245526 mm Hg (calculated value)
Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

Other safety characteristics

VOC content	:	2.13757915 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Ethylene brassylate (105-95-3)	
LD50 oral rat	> 5000 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)

Cedryl acetate (77-54-3)	
LD50 oral rat	44750 mg/kg (Source: NLM_CIP)

tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (63500-71-0)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)

Patchouli oil (8014-09-3)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)

Linalyl acetate (115-95-7)	
LD50 oral rat	14550 mg/kg (Source: EPA_HPV)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)
LC50 Inhalation - Rat	> 18.94 mg/l (Exposure time: 8 h Source: ECHA)

Cashmeran (33704-61-9)	
LD50 oral rat	2685 mg/kg (Source: ECHA_API)
LD50 oral	2900 mg/kg

(ETHOXYMETHOXY)CYCLODODECANE (58567-11-6)	
LD50 oral rat	> 5 g/kg (Source: ECHA)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)

Carbitol (111-90-0)	
LD50 oral rat	10502 mg/kg (Source: OECD_SIDS)
LD50 dermal rabbit	9143 mg/kg (Source: OECD_SIDS)
LC50 Inhalation - Rat	> 5240 mg/m³ (Exposure time: 4 h Source: NLM_CIP)

Clove Leaf Oil (8000-34-8)	
LD50 oral rat	1370 mg/kg (Source: NZ_CCID)
LD50 oral	2650 mg/kg
LD50 dermal rabbit	1200 mg/kg (Source: NLM_CIP)

COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)

COUMARIN (91-64-5)	
LD50 dermal rat	293 mg/kg (Source: ECHA_API)

Linalool (78-70-6)	
LD50 oral rat	2790 mg/kg (Source: NLM_CIP)
LD50 oral	2790 mg/kg
LD50 dermal rabbit	5610 mg/kg (Source: ECHA_API)

Orange oil (8008-57-9)	
LD50 oral rat	4400 mg/kg (Source: NZ_CCID)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)

Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

COUMARIN (91-64-5)	
IARC group	3 - Not classifiable

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Cashmeran (33704-61-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Toluene (108-88-3)	
Hydrocarbon	Yes

11.2. Information on other hazards

Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Toxic to aquatic life with long lasting effects.

Linalyl acetate (115-95-7)	
LC50 - Fish [1]	11 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through] Source: ECHA)

Cashmeran (33704-61-9)	
LC50 - Fish [1]	10.3 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)

Carbitol (111-90-0)	
LC50 - Fish [1]	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	19100 – 23900 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through] Source: EPA)
EC50 - Crustacea [1]	3940 – 4670 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Linalool (78-70-6)	
LC50 - Fish [1]	27.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA)
EC50 - Crustacea [1]	20 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

OUD & AMBER CLP #EU58083F	
Persistence and degradability	Not established.

Ethylene brassylate (105-95-3)	
Persistence and degradability	May cause long-term adverse effects in the environment.

Cedryl acetate (77-54-3)	
Persistence and degradability	Rapidly degradable

reaction mass of: (E)-oxacyclohexadec-12-en-2-one; (E)-oxacyclohexadec-13-en-2-one; a) (Z)-oxacyclohexadec-(12)-en-2-one and b) (Z)-oxacyclohexadec-(13)-en-2-one (111879-80-2)	
Persistence and degradability	Rapidly degradable

tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (63500-71-0)	
Persistence and degradability	Rapidly degradable

Patchouli oil (8014-09-3)	
Persistence and degradability	Rapidly degradable

Linalyl acetate (115-95-7)	
Persistence and degradability	Rapidly degradable

Cashmeran (33704-61-9)	
Persistence and degradability	Rapidly degradable

Sandal Mysore Core (28219-60-5)	
Persistence and degradability	Rapidly degradable

(ETHOXYMETHOXY)CYCLODODECANE (58567-11-6)	
Persistence and degradability	May cause long-term adverse effects in the environment, Not established.

Carbitol (111-90-0)	
Persistence and degradability	Rapidly degradable

Clove Leaf Oil (8000-34-8)	
Persistence and degradability	Rapidly degradable

COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable

Linalool (78-70-6)	
Persistence and degradability	Rapidly degradable

Orange oil (8008-57-9)	
Persistence and degradability	Rapidly degradable

Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable

Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

OUD & AMBER CLP #EU58083F	
Bioaccumulative potential	Not established.

Ethylene brassylate (105-95-3)	
Partition coefficient n-octanol/water (Log Pow)	4.3 (at 25 °C (at pH 6.4-7)
Bioaccumulative potential	Not established.

Cedryl acetate (77-54-3)	
Partition coefficient n-octanol/water (Log Pow)	6 (at 25 °C)

tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (63500-71-0)	
Partition coefficient n-octanol/water (Log Pow)	1.65 (at 23 °C (at pH >6.09-<6.74)

Patchouli oil (8014-09-3)	
Partition coefficient n-octanol/water (Log Pow)	Not established

Linalyl acetate (115-95-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 (at 25 °C)

Cashmeran (33704-61-9)	
BCF - Fish [1]	(81 dimensionless (whole body w.w.)
Partition coefficient n-octanol/water (Log Pow)	4.2 (at 20 °C)

Sandal Mysore Core (28219-60-5)	
Partition coefficient n-octanol/water (Log Pow)	3.8

(ETHOXYMETHOXY)CYCLODODECANE (58567-11-6)	
BCF - Fish [1]	(530 dimensionless (whole body w.w.)
Partition coefficient n-octanol/water (Log Pow)	5.4 (at 25 °C)
Bioaccumulative potential	Not established.

Carbitol (111-90-0)	
Partition coefficient n-octanol/water (Log Pow)	-0.8

COUMARIN (91-64-5)	
Partition coefficient n-octanol/water (Log Pow)	≥ 1.91 – ≤ 1.51 (at 25 °C (at pH 7)

Linalool (78-70-6)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 20 °C (at pH 7)

Orange oil (8008-57-9)	
Partition coefficient n-octanol/water (Log Pow)	≥ 2.78 – ≤ 4.88

Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)

Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

OUD & AMBER CLP #EU58083F	
Other information	Avoid release to the environment.

Ethylene brassylate (105-95-3)	
Other information	Avoid release to the environment.

(ETHOXYMETHOXY)CYCLODODECANE (58567-11-6)	
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecological waste information : Avoid release to the environment.

HP Code : HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate)	Environmentally hazardous substance, liquid, n.o.s. (Cedryl acetate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Cedryl acetate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedryl acetate), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6


Special provisions (ADR) : 274, 335, 375, 601, 650

Limited quantities (ADR) : 5l

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1

Mixed packing provisions (ADR)	:	MP19
Portable tank and bulk container instructions (ADR)	:	T4
Portable tank and bulk container special provisions (ADR)	:	TP1, TP29
Tank code (ADR)	:	LGBV
Vehicle for tank carriage	:	AT
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V12
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV13
Hazard identification number (Kemler No.)	:	90
Orange plates	:	
Tunnel restriction code (ADR)	:	-
EAC code	:	•3Z

Transport by sea

Special provisions (IMDG)	:	274, 335, 375, 969
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	LP01, P001
Special packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1, TP29
Stowage category (IMDG)	:	A

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y964
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	964
PCA max net quantity (IATA)	:	450L
CAO packing instructions (IATA)	:	964
CAO max net quantity (IATA)	:	450L
Special provisions (IATA)	:	A97, A158, A197, A215
ERG code (IATA)	:	9L

Inland waterway transport

Classification code (ADN)	:	M6
Special provisions (ADN)	:	274, 335, 375, 601, 650
Limited quantities (ADN)	:	5 L
Excepted quantities (ADN)	:	E1
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP
Number of blue cones/lights (ADN)	:	0

Rail transport

Classification code (RID)	:	M6
Special provisions (RID)	:	274, 335, 375, 601, 650
Limited quantities (RID)	:	5L
Excepted quantities (RID)	:	E1
Packing instructions (RID)	:	P001, IBC03, LP01, R001
Special packing provisions (RID)	:	PP1
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1, TP29
Tank codes for RID tanks (RID)	:	LGBV
Transport category (RID)	:	3

Special provisions for carriage – Packages (RID)	:	W12
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW13, CW31
Colis express (express parcels) (RID)	:	CE8
Hazard identification number (RID)	:	90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	**Applicable on**	**Entry title or description**
3(a)	Orange oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	OUD & AMBER CLP #EU58083F ; Cedryl acetate ; Florol ; Patchouli oil ; Linalyl acetate ; Cashmeran ; Sandal Mysore Core ; (ETHOXYMETHOXY)CYCLODODECANE ; Clove Leaf Oil ; Linalool ; Orange oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	OUD & AMBER CLP #EU58083F ; Ethylene brassylate ; Cedryl acetate ; Oxacyclohexadec-12-en-2-one, (12E)- ; Patchouli oil ; Cashmeran ; Sandal Mysore Core ; (ETHOXYMETHOXY)CYCLODODECANE ; Orange oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
48.	Toluene	Toluene

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 2.13757915 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

National regulations

Austria

Toxic Substances Ordinance 2000 : Is not subject to the Toxic Substances Ordinance 2000.

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

VOC ordinance (ChemVOCFarbV) : VOC content : 2.13757915 % (calculated value)(CARB VOC) (%w/w)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Major Accidents Ordinance (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : Orange oil is listed

SZW-lijst van mutagene stoffen : Orange oil is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : Toluene is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with it.

If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.

Poland

Polish National Regulations : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as ammended)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.

Full text of H- and EUH-statements:	
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.